Honeywell

DL1000 Electrode Mountings

(Durafet II pH Electrodes & Mountings for DL421 with and without Vario PinDurafet Connectors)

Model Selection Guide 51-52-16-72 Issue 6

Section 2 Page: DL-3

Effective Date: March 22, 2004


Model Selection Guide with Price Data


Honeywell Proprietary











Instructions

- Select the desired key number. The arrow to the right marks the selection available.
- Make the desired selections from Table I using the column below the proper arrow.
 A dot (•) denotes availability. No (•) dot denotes not available.

Key Number I II

List Price equals the sum of all prices for all selections made.

Selection Availability

Key Number - Mounting/Electrode Only - (Note 1) (Specify DL421 separately)

TABLE I - INSTALLATION MOUNTING TYPE (Note 2)

TABLE 1- INSTALLATION INCONTING TITLE (Note 2)								
Pipeline Bushing (7758)	Bushing Material of Construction		Polypropylene	581	•			
(Remote DL421 Mtg. Only)			316SS	582	•			
Insertion/Removal (7774)	Ball Valve Assembly Material		CPVC	741	•			
(Remote DL421 Mtg. Only)	of Construction		316SS	742	•			
In-Line (7777)	1 in. (2,54 cm) Electrode Suitable		Remote DL421 Mtg w/PWB connector	771	•			
	for 3/4" Pipe Tee		Integral DL421 Mounting	772	•			
			Remote DL421 Mtg w/VarioPin connector	774	•			
Immersion (7777) 1 in. (2,54 cm) Electrode Suitable for Immersion Applications		trode Suitable	Remote DL421 Mtg w/PWB connector	773	•			
		ications	Remote DL421 Mtg w/VarioPin connector	775	•			
		1.5 in. (3,81cm)	flange - 2.29 in. (5,82cm) immersion	941	•			
Sanitary Durafet	Shallow Insertion 2 in. (5,08 cm) flange - 2.83 in. (7,19 cm) immersion		942	•				
Vario Pin Connector	3 in. (7,62 cm) fla		ange - 2.53 in. (6,43 cm) immersion	943	•			
(Remote DL421 Mtg Only)	emote DL421 Mtg Only) 1.5 in. (3,81cm) flange - 2.91 in. (7,39cm) immersion		944	•				
			ange - 3.72 in. (9,45 cm) immersion	945	•			
			ange - 3.73 in. (9,47 cm) immersion	946	•			

Section 2 Page: DL-4

Effective Date: March 22, 2004

TABLE II - OPTIONS Selection Availability

	·			,	
Tagging	None	00	•		
	Stainless Steel Customer I.D. Tag - 3 lines w/22 characters/line	SS	•		
Calibration Certificate	None	00	•		
	Calibration certificate to be supplied w/shipment	10	•		

Notes:

- 1. DL421 electronics module must be specified separately
- 2. Replacement electrodes for these mountings can be ordered as follows:
- 3. Users of the old card edge style sanitary durafet connector must upgrade their remote cable to P/N TBD

Replacement Electrode

Table I Selection	Mounting Type	Part Number
581	Pipeline Bushing (7758)	51204976-001
582	Pipeline Bushing (7758)	51204976-001
741	Insertion Removal - CPVC (7774)	51205554-002
742	Insertion Removal - 316 SS (7774)	51204976-001
771	In-Line Remote DL421 (7777) w/PWB connector	51205554-001
772	In-Line Integral DL421 (7777) w/PWB connector	51500258-001
773	Immersion/ Remote DL421 (7777) w/PWB connector	51205554-002
774	In-Line Remote (7777) w/Vario Pin connector	51453503-001
775	Immersion/ Remote (7777) w/Vario Pin Connetor	51453503-005
941	1.5 in. (3,81 cm) flange, Shallow Immersion w/PWB connector	51453535-001
942	2 in. (5,08 cm) flange, Shallow Immersion w/PWB connector	51453535-003
943	3 in. (7,62 cm) flange, Shallow Immersion w/PWB connector	51453535-005
944	1.5 in. (3,81 cm) flange, Deep Immersion w/PWB connector	51453535-002
945	2 in. (5,08 cm) flange, Deep Immersion w/PWB connector	51453535-004
946	3 in. (7,62 cm) flange, Deep Immersion w/PWB connector	51453535-006