



eCAL Temperature/Process Controller

Compact, Cost-effective, Extended capabilities



eCAL is a general-purpose temperature and process controller ideal for industrial and scientific processing equipment

Adding value within a cost frame

The CAL Controls product line of West Control Solutions is recognised globally in the market as an offering of cost-effective controllers with unrivalled sales and customer support and adding specific value in the area of design, usability and serviceability. The addition of the eCAL controller reinforces this unique positioning of the CAL Controls product family.

The markets for industrial temperature and process controllers demand not only a cost-effective and compact solution, but also added value to the overall competitiveness of the machine or equipment. On top of this the eCAL controller delivers an improved aesthetic design and enhanced functionality.

Applications

- Small lab and industrial ovens
- Incubators
- Chillers
- Bag Sealers
- Sterilisers
- Fluid Baths
- Small Packaging Machines
- Dryers
- Food and beverage processing
- Plastics extrusion

And many more ...



Food and beverage



Life sciences



Ovens and furnaces



Plastics and packaging

eCAL—Features meeting requirements



only 70 mm—reduced depth behind panel

only 70 mm—reduced depth behind panel

- easier to install
- ideal for retrofit

Cost-effective control—high functionality

- Universal input—one input for all sensor types
- Alarms and diagnostics—prevent problems before they happen
- Temperature profile control with programmer function

Available in 1/16 DIN (48mm x 48mm) and 1/8 DIN (96mm x 48mm) formats.

Input

- Universal input for Thermocouple, PT100 or linear DC sensors

Alarms and Diagnostics

- Two absolute or deviation alarms—high, low or band
- Loop alarm
- Clear on-screen status messages ‘alm’
- Relay life monitor
- High ambient temperature warning

Communications or networking

- RS485 Modbus RTU communications option



User interface

- Clear LED display with 4 digits upper and lower
- 4 button membrane keypad including function button for auto/manual or profiler control
- 3 output status LEDs

Outputs

- Output types: relay, SSR drive or linear DC
- 2 or 3 fixed outputs

Programmer function

- 2 programs of up to 16 segments
- Delay timer
- Auto holdback function – guaranteed soak
- Ramp, dwell, step, events, loop
- Function button for profiler control (run, hold, stop, reset)

Control

- PID or ON/OFF control
- ‘Heat’ or ‘Heat/Cool’ operation
- Manual or auto pre-tune

Specifications

(for detail specs see Datasheet Ref – DS-EC01-1-EN-1209)

HMI

Interface	4 button operation, dual 4 digit 10mm & 8mm high visibility LED displays, plus 3 LED indicators for output status Function button: Profiler control (run, hold, stop, reset) or auto / manual control (user defined)
-----------	---

Input

Thermocouple	J, K, B, C, D, L, N, R, S, T, PtRh 20%:40%
RTD	3 wire PT100,
DC Linear	0 to 20mA, 4 to 20mA, 0 to 50mV, 10 to 50mV, 0 to 5V, 1 to 5V, 0 to 10V, 2 to 10V
Measurement Accuracy	±0.1% of full range, ±1LSD (for additional accuracy details see specification)
Sensor Break Detection	Thermocouple , RTD & linear DC (4-20mA, 1-5V and 2-10V only)

Control

Control Types	Full PID or on-off control, heat only, cool only or heat & cool
Tuning Types:	Automatic pre-tune and manual tuning.

Profiler

Number of programs	2, each with 16 free-form segments (ramp /dwell / step / end) maximum segment length: 99Hrs 59 Mins
Delay timer start	Max 99 hours 59mins delay from initiation to program start
Guaranteed soak / Auto hold	Holds program if PV out of specified hold band during dwell segments
Program cycles	1 to 9999 or infinite (continuously restarts program at end)
Power loss recovery	Continue profile from point of power fail or end profile and return to controller mode

Alarms

Alarm types	Process High, process low, band and deviation (high or low) alarm
-------------	---

Outputs

Output Configuration	Output 1 & 2; relay or SSR Drive, output 3; relay, SSR Drive, linear DC (mA/V), RS485 comms
Control & Alarm Relays	Contacts SPST 2 amp resistive at 120/240V AC
SSR Driver Outputs	Drive capability >10V DC
DC Linear Outputs	0 to 20mA, 4 to 20mA, 0 to 10V, 2 to 10V, 0 to 5V

Operating and Environmental

Temperature	0 to 55°C operating
Power Supply	100 to 240V 50/60Hz ±10% or optional 20 to 48VAC 50/60Hz, 22 to 55VDC low voltage version
Front Panel Protection	IP66 (IP20 behind panel)

Conformance

Standards	CE
EMI: & Safety	Complies with EN61326 & EN61010-1, pollution degree 2, installation category II

Weights & Dimensions

Dimensions	1/16 DIN, 48 x 48mm; 1/8 DIN, 96 x 48mm; 70mm depth behind panel
Weight	156 g, 210 g

WEST
Control Solutions

WEST Control Solutions — your global partner for temperature and process control

Austria

PMA Prozeß- und Maschinen-Automation GmbH
Liebermannstraße F01 · 2345 Brunn am Gebirge
Tel.: +43 (0)2236 691-121 · Fax: +43 (0)2236 691-102
info@pma-online.at

China

Danaher Setra-ICG
Tianjin Co. · Ltd. No. 28 Wei 5 Road
The Micro-Electronic Industry Park TEDA
Xiqing District · Tianjin 300385
Tel.: +86 22 8398 8098 · Fax: +86 22 8398 8099
Sales Hotline: +86 400 666 1802
tc.sales@danaher.com

France

Hengstler SA · 69 Rue de la Belle Etoile
Bat D - ZI Paris Nord II · 95700 Roissy
Tel.: +33 (1) 77 80 90 40 · Fax: +33 (1) 77 80 90 50
info@westinstruments.com

Germany

PMA Prozeß- und Maschinen-Automation GmbH
Miramstraße 87 · 34123 Kassel
Tel.: +49 (0)561 505-1307 · Fax: +49 (0)561 505-1710
mailbox@pma-online.de

United Kingdom

WEST Control Solutions
The Hyde Business Park
Brighton · East Sussex · BN2 4JU
Tel.: +44 (0)1273 606271 · Fax: +44 (0)1273 609990
info@westinstruments.com

USA

WEST Control Solutions
1675 Delany Road · Gurnee · IL 60031-1282
Tel.: 800 866 6659 · Fax: 847 782 5223
custserv.west@dancon.com

Brochures and datasheets are available for the complete range of WEST Control Solutions products, contact your local sales office for more information or visit our website at: www.west-cs.com



WEST **Partlow**

BR-EC-2-EN-0310